

PRO® 46

Colored Crepe Paper Tape



Technical Data Sheet

Pro® 46 is a rubber based colored crepe paper tape.

Features & Benefits:

Adhesive system designed for excellent performance and adhesion to a variety of smooth substrates
Resists solvents and oil
Premium Grade
Printable
Flexible

Technical Data

- ⇒ Adhesive: Rubber based
- ⇒ Backing: Colored Crepe Paper
- ⇒ Tensile strength: 18 lbs. per inch
- ⇒ Elongation: 8%
- ⇒ Total Tape Thickness: 4.7 mils
- ⇒ Adhesion to steel: 33 oz. per inch
- ⇒ Temperature Range: 60°F to 150°F
- ⇒ ASTM 6123/ D6123M-07 Type II, Conforms to ASTM D-4236 (Contains no heavy metals)
- ⇒ Colors: Yellow, White, Pink, Black, Red, Orange, Green, Lt. Green, Blue, Lt. Blue, Purple, Grey

Application:

Pro® 46 is used on a wide variety of smooth substrates as a printed or unprinted general purpose tape. Pro® 46 can be used for packaging, bundling, binding, holding, splicing, banding, labeling, color coding, decorating and identification.



621 Route One South. North Brunswick, NJ 08902
Toll Free #1-800-345-0234
sales@protapes.com

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications. Tape should be stored in its original packaging in a cool dry area away from direct sunlight and should be used within 12 months from date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.